



GROUT FILLER

Product Description

It is a grout filler material for cement based, ceramic and natural stone.

Areas of Use

- In internal spaces
- In horizontal and vertical grouting
- Natural stone, ceramic, dolomite stone, pressed brick, glass mosaic

Features and Benefits

- Easy to prepare and apply
- Provides smooth surface
- High adhesion
- Does not crack
- Long working time

Surface Preparation

Natural stone, cerami, dolomite stone, pressed brick, granite and other coating materials must be cleaned of dirt, and cleaned well with a wet sponge before application, and excess water must be removed.

Application Instructions

- Mix 20 Kg IKS Grout Filler with 6-7 liters of water to obtain a homogeneous mixture. Wait 3-5 minutes and then mix again for 1-2 minutes before applying.
- In horizontal and vertical applications, apply the product to the surface using a rubber trowel.

Appearance	White, Grey and Colored powder
Grout filler material	Contains silicone and non-silicone products in 2 different types
Mixing Ratio	6-7 lt water / 20kg powder
Consumption	4-5 kg / m ²
Application Temperature	Between +5°C and +35°C
Shrinkage	≤ 3 mm/m
Water absorption after 30 min	≤ 5 gr
Water absorption after 4 hours	≤10 gr
Flexural strength	≥ 2,5 N/mm ²
Compressive strength	≥ 15 N/mm ²
Compressive strength after freeze-thaw cycle	≥ 15 N/mm ²